

BAV361, BAV362, BAV363, BAV465



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase or single phase as option up to 2.2 kW
- Filter body Ø360 and for mod. BAV465, Ø460
- Star filter of polyester cat. "L"
- Manual filter shaker
- Straight inlet Ø50mm
- For model BAV465, quick inlet Ø70mm
- Fairing with support feet
- Standard version painted RAL 9003 (white)
- X1 version with filter chamber in stainless steel and fairing in painted steel
- X2 version all in stainless steel
- T version: with magneto-thermal switch into IP 55 box, optionally

		BAV361	BAV362	BAV363	BAV465
Tension /Voltage	Volts	3~ 230-400V/50Hz	3~ 230-400V/50Hz	3~ 230-400V/50Hz	3~ 400V/50Hz *
Power	kW	0.90	1.5	2.2	4
Depression max	mbar	230	250	310	320
Max working depression	mbar	150	210	200	200
Max air flow	m ³ /h	150	210	310	520
Primary filtering surface	m ²	0,70	0,70	0,70	1,9
Absolute filtering surface	m ²	3,1	3,1	3,1	3,1
Container capacity	Lt	12	12	12	25
Product inlet	mm	Ø50	Ø50	Ø50	Ø70
Noise level	DbA	70	64	73	76
Overall dimensions	Cm	51x56x105h	51x56x105h	51x56x105h	60x70x150h
Weight	Kg	40	48	54	95
Protection	IP	54	55	54	54

* other voltages and frequencies available on request