

A1046ECO1.3D, A1046KECO1.3D



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous marked ATEX EX II 3D put into a protective housing in the back side of the vacuum cleaner
- Electric cable 10m long with industrial plug 3Ph+earth 16A - IP 67
- Vacuum-meter to check filter efficiency
- Manual filter shaker on top of the filter chamber for the filter cleaning
- 100lt container equipped with wheels and side handles for emptying and optional lifting strap for forklift truck
- Quick inlet Ø70 for easy attachment of accessories
- Standard version with container in stainless steel, filter chamber and frame painted Ral 7001 grey
- Fixed wheels Ø150mm and pivoting wheels with brake Ø125mm

		A1046ECO1.3D	A1046KECO1.3D
Tension/Voltage	Volts	3~ 400-690V/50Hz	3~ 400-690V/50Hz
Plug	A	3P + T 16A IP67	3P + T 16A IP67
Power	KW	7,5	7,5
Depression max	mbar	350	260
Max working depression	mbar max	320	280
Max air flow	m ³ /h	540	700
Primary filter surface	m ²	2,6	2,55
Absolute filter surface	m ²	7,5	7,5
Container capacity	Lt	100	100
Product inlet	mm	70	70
Noice level	DbA	76	76
Overall dimensions	Cm	65X120X175h	65X120X175h
Weight	Kg	170	170
Protection	IP	55	55